



SKU	Designation	French Law	Length (cm)	Width (cm)	Height (cm)	Weight (g)	Objectif Diam. (mm)	Reticle	MSRP
A67011	RED DOT SIGHT UTG 3 MOA	Vente libre	5.7	3.8	6.8	153	18 mm	Dot 3 MoA	252.00 € incl. tax

A reliable and efficient red dot with a complete package.

- Precision machined from 6061-T6 aluminum and finished with a matte black anodize
- 3 MOA red dot with 8 brightness settings
- IPX7 waterproof rating
- 21mm low profile quick release (QR) mount with lower 1/3 Co-witness riser included

Comes with: 3mm Allen key, T25 Torx key, W/E adjustment key, CR2032 battery, neoprene cover

Description

- Precision machined from 6061-T6 aluminum and finished with a matte black anodize
- Wide field of vision Objective lens diameter 18 mm
- Impact-resistant tempered glass lens
- 3 MOA red dot with 8 brightness settings
- Over 30,000 hours of battery life at medium brightness setting
- Flush-mounted, snag-free turrets with precise 1 MOA per click adjustment at 100 yards
- IPX7 waterproof rating
- ACOG® Mini Low Profile Quick Release (QR) Mount with Lower 1/3 Co-witness Riser Included
- **NOTE:** We recommend tightening the M5 screw to approximately 25 in-lbs of torque.

Accessories included

- Round head screws M5x0.8-5mm length, X2
- 3 mm Allen key
- Torx T25 key
- W/E adjustment key

- CR2032 3V high energy lithium battery
- Neoprene viewfinder cover
- Cleaning cloth
- User Manual

UTG® ACCU-SYNC® Dot Sights are available in a compact and subcompact size and feature a 3 MOA illuminated red dot with 8 manually adjustable brightness intensity settings to choose from. Illumination memory allows users to easily return to the last brightness setting used upon activation. Fully sealed, ACCU-SYNC® Dot Sights are IPX7 waterproof and constructed of matte black anodized 6061-T6 aluminum. Optimized for low power consumption and powered by a single CR2032 battery, a battery life of over 30,000 hours (at medium brightness) comes standard.

The mounting base utilizes the common mini ACOG® footprint and is configured for a lower 1/3 co-witness right out of the box. Removing the included riser lowers the height to that of a low mount, giving users two commonly used height profiles for different firearm applications. Additionally, the base features square recoil stops and our QR (quick release) mount, allowing for quick installation and removal, reliable return to zero, and compatibility with Picatinny rails that may be even out-of-spec widths. The tool-free tension adjustment is locked in place via a gear and spring-loaded locking lever interface, allowing users to set it once and forget it.

QUICK TO ACQUIRE AND PAY

- Low profile quick release (QR) bracket with tool-free tension adjustment
- Configured for a lower 1/3 co-witness and compatible with the Mini ACOG® impression
- Flush-mounted, snag-free turrets with precise 1 MOA per click adjustment at 100 yards
- Multi-coated lens with a wide 18mm field of view

RELIABLE PERFORMANCE

- IPX7 Waterproof Operating Range
from -40°F to 158°F
- Recoil rated up to .450 Bushmaster
Squared Recoil Stops for a safe and repeatable zero
- Quick-release locking lever prevents accidental release

SUSTAINABLE CONSTRUCTION

- Precision machined matte black anodized 6061-T6 aluminum construction
- Reinforced main body and recessed windage and elevation turrets
- Impact-resistant tempered glass lens

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.